

ROOFWALK SPECIFICATIONS

Roofwalk (24" / 36" / 48" wide) to be furnished by LMCurbs, 827 Fisher Road, Longview, Texas 75604, 1-903-297-2148, 1-800-284-1412, Fax # 903-759-3598.

Grating shall be provided in areas detailed on drawings and shall be furnished in individual units 12" wide. Grating shall be furnished in single, unspliced sections for all requirements up to 24' in length. Grating shall interlock, with male-female (M-F) legs providing a friction lock, so that no horizontal movement between units can occur. The outside leg of all runs shall be male.

Material to be 12" wide x 20' and 24' long sections of anti-skid planking in 18 ga. galvanized steel (G-90 coating) with 2-1/2" leg height. Support plate assemblies and attachment hardware for parallel installation are to be installed 5'- 6' centers and attachment hardware for perpendicular installation are to be installed on 8' centers. All mounting hardware is furnished in electro-galvanized, paint grip finish, or aluminum. Note: Field cutting of the roofwalk planking will be required.

Suitability of any S-5! assembly and walkway system for local area and job conditions is the responsibility of the designer or architect /engineer. Roof panels must be adequately attached to structure or substrate. All loads incurred by the S-5! Assembly and walkway system will be transferred to the panels.